



ANH Refractories Europe Ltd

Dock Road South, Bromborough

Wirral, England, CH62 4SP

Tel +44 (0)151 641 5900

Fax +44 (0)151 641 5910

Email sales@anheurope.co.uk

Web www.anheurope.co.uk

Instructions For Mixing and Using Sairset

This product is an air setting mortar designed for laying brick.

Some liquid may be on the top surface of the mortar as received. This liquid should **NEVER BE Poured OFF** but thoroughly mixed back into the mortar before any material is removed from the pail, ensure any mixing equipment used is clean.

Ideally, the entire pail of SAIRSET should be used once the lid has been removed. If this is not possible, it is important to replace the lid firmly before storage as SAIRSET will harden on contact with air.

Thin brick joints give the best results, each joint should be completely filled with mortar.

The shelf life of SAIRSET is 12 months from the date of manufacture providing the material has been stored under suitable conditions.

For best results, SAIRSET should be stored in a temperature controlled warehouse between 10 and 25°C. If this is not possible, SAIRSET should be stored out of direct sunlight in a warehouse. In hot climates storage in a shipping container or other similar vessel is not suitable as the temperature within the container will be too high, this will adversely affect the SAIRSET and result in a reduced shelf life. Freezing of this product will not have any detrimental effect, although it must be thawed thoroughly prior to use.

